

Door & Window Size Schedule (India 2025)

Contractor-Ready | Feet + mm | Room-Wise Standards

A practical sizing reference for homeowners, architects, contractors, and carpenters

Door Schedule

S.No	Door Location	Door Type	Size (ft)	Size (mm)	Thickness	Material	Opening Direction	Qty	Notes
1	Main Entrance	Single Flush / Panel	7 × 3.5	2134 × 1067	40–45 mm	Teak / Solid Wood	Inside	1	Safety lock + viewer
2	Living Room	Wooden Flush	7 × 3	2134 × 914	32–35 mm	Flush / Laminated	Inside	1	
3	Bedroom	Flush Door	7 × 3	2134 × 914	30–35 mm	Flush + Laminated	Inside		
4	Kitchen	Flush Door	7 × 2.75	2134 × 838	30–35 mm	BWP Ply Suggested	Inside		
5	Bathroom / WC	PVC / Flush	7 × 2.25	2134 × 686	30–32 mm	PVC / Waterproof	Outside		Vent gap if needed
6	Balcony	Glass / Sliding	7 × 6 / 8 × 6	2134 × 1829 / 2438 × 1829	35 mm frame	Aluminium + Glass	Sliding		2/3 track
7	Pooja Room	Wooden	7 × 2.5	2134 × 762	30–35 mm	Wood / Glass option	Inside		
8	Store Room	Flush	7 × 2.5	2134 × 762	30 mm	Flush	Inside		
9	Terrace	Metal / Glass	7 × 3	2134 × 914	35–40 mm	Metal/Aluminium	Outside		Weather proof

Window Schedule

S.No	Window Location	Window Type	Size (ft)	Size (mm)	Sill Height	Glass / Frame	Track	Qty
1	Living Room	Sliding / Casement	5 × 4 or 6 × 4	1524 × 1219 / 1829 × 1219	2–2.5 ft	Aluminium + 5mm Glass	2 or 3	
2	Bedroom	Sliding	4 × 4	1219 × 1219	2–2.5 ft	Aluminium + 5mm Glass	2	
3	Kitchen	Sliding	4 × 3	1219 × 914	3.5–4 ft	Aluminium + 5mm Glass	2	
4	Bathroom	Ventilator	2 × 1.5	610 × 457	5 ft	Frosted Glass	Fixed / 1 track	
5	Staircase	Fixed / Louver	3 × 2	914 × 610	5.5–6 ft	Glass/Aluminium	Fixed	
6	Balcony	Sliding	6 × 4	1829 × 1219	2–2.5 ft	Aluminium + Glass	2/3 track	
7	Corridor	Fixed / Sliding	4 × 2	1219 × 610	6 ft	Glass	Fixed	

Ventilator / Loft Window Schedule

S.No	Location	Size (ft)	Size (mm)	Type	Qty
1	Above Main Door	3 × 1	914 × 304	Fixed Glass	
2	Bathroom Top Vent	1.5 × 1	457 × 304	Louver / Fixed	
3	Kitchen Top Vent	2 × 1	610 × 304	Exhaust Vent	

Hardware & Fittings Checklist

Item	Specification
Door Handle Height	1050 mm (3.5 ft from floor)
Main Door Lock	10–12 lever or Smart Lock
Hinges	4-inch SS heavy-duty
Sliding Track	2 or 3 track aluminium
Door Stopper	Magnetic or Rubber
Tower Bolt	8–10 inch SS
Door Frame	4.5-inch frame standard

Notes for Site Execution

- Maintain **uniform 7 ft door height** for visual harmony.
- Keep a **minimum of 10% of carpet area as an openable window** for ventilation.
- **Bathroom doors open outside**, all others preferably inside.
- Allow **track + grill clearance** for sliding windows.
- Avoid random custom sizes to **reduce cost by 15–30%**.

© 2025 Houseyog.com — Smart Home Design & Construction Planning in India.

 www.houseyog.com

 help@houseyog.com

 Mob: +9175960 58808